

# JF-ADVR-B7204/B7208/B7216

## 4ch/8ch/16ch Fribrid 1080P 2HDD ADVR



### Features

- ◆ Support 4ch/8ch/16ch 1080P Unreal-time Encoding
- ◆ Support AHD/TVI/CVI/CVBS/IP Self-adaptive
- ◆ HDMI/VGA Simultaneous Video Output
- ◆ Support DHCP,FTP,DNS,DDNS,NTP,UPNP,EMAIL,3G,WIFI
- ◆ Support ONVIF Protocol
- ◆ Support WEB,VMS,MYEYE Platform
- ◆ Support Mobile Phone Monitoring(IOS ,Android)
- ◆ Cloud Services,P2P,Alarm Information Push To Phone
- ◆ Support Multi-Language

### Dimensions



# JF-ADVR-B7204/B7208/B7216

## 4ch/8ch/16ch Fribrid 1080P 2HDD ADVR

### Specification

2HDD				
Model	JF-ADVR-B7204	JF-ADVR-B7208	JF-ADVR-B7216	
Video				
Encode	4CH*1080P@15fps	8CH*1080P@12fps	16CH*1080P@12fps	
Playback	4CH*1080P@15fps	4CH*1080P@12fps	16CH*1080P@12fps	
Multi-Mode	Analog	4CH*1080P	8CH*1080P/8CH*1080N	16CH*1080P/16CH*1080N
	Hybrid	4CH*1080N(Analog)+ 4CH*960P(IP)	4CH*1080P(Analog)+ 4CH*1080P(IP)	8CH*1080P(Analog)+ 8CH*1080P(IP)
	IP	16CH*1080P/9*1080P/ 16CH*960P/4CH*5M	8CH*1080P+8CH*960P/ 16CH*960P/4CH*3M/4CH*5M	8CH*1080P+8CH*960P/ 8CH*3M/4CH*5M
Video Compression	H.264			
Audio				
Audio Compression	G.711A			
Interface				
Video Input	4*BNC	8*BNC	16*BNC	
Video Output	1*VGA,1*HDMI			
Audio I/O	4/1	8/1	6/1	
Alarm I/O	4/1			
Ethernet	1*10/100Mbps Ethernet port, RJ45 port			
PTZ Control	1*RS485, Support for multiple PTZ protocol			
USB	2*USB2.0			
Max HDD	2*8TB			
General				
Temperature	0 °C - + 55 °C			
Humidity	10% -90% RH			
Power	12V/4A			
Consumption	<15W(Without HDD )			
Dimension	310mm(L)* 298mm(W)* 60mm(H)			

JF TECH Co.,Ltd.  
Headquarters(Hangzhou):  
Building 9, Yinhu Innovation Center, Hangzhou, China  
Business Center(Shenzhen):  
A 7th Floor, Block Sakata 5 Avenue and Chong Hing Times Tower Shenzhen  
All Rights Reserved • Specifications subject to change without notice.

Website:<http://www.jftech.com>  
Tel:+86-0571-23271188  
Tel:+86-0755-32898088