

# JF-ADVR-B7404L/B7408L/E7416L

4ch/8ch/16ch Fribrid 4MP/5MP Lite 2HDD ADVR



## Features

- ◆ Support 4ch/8ch/16ch 5MP Unreal-time Encoding
- ◆ Support XVI/AHD/TVI/CVI/CVBS/IP Self-adaptive
- ◆ HDMI/VGA Simultaneous Video Output
- ◆ Support DHCP,FTP,DNS,DDNS,NTP,UPNP,EMAIL,3G,WIFI
- ◆ Support ONVIF Protocol
- ◆ Support WEB,VMS,MYEYE Platform
- ◆ Support Mobile Phone Monitoring( IOS ,Android)
- ◆ Cloud Services,P2P,Alarm Information Push To Phone
- ◆ Support Multi-Language

## Dimensions



# JF-ADVR-B7404L/B7408L/E7416L

4ch/8ch/16ch Fribrid 4MP/5MP Lite 2HDD ADVR

## Specification

2HDD			
Model	JF-ADVR-B7404L	JF-ADVR-B7408L	JF-ADVR-E7416L
Video			
Encode	4CH *5M @11fps	8CH*5M@11fps	16CH*5M@11fps
Playback	4CH*5M@11fps	8CH*5M @11fps	8CH*5M@11ps
Multi-Mode	Analog	4CH*5M	16CH*5M
	Hybrid	2CH*5M(Analog)+2CH*5M(IP)	4CH*5M(Analog)+4CH*5M(IP)
	IP	8CH*1080P+8CH*960P/ 4CH*3M/4CH*5M	8CH*3M/4CH*5M 32*1080P/16CH*3M/8CH*5M
Video Compression	H.264/H.264+		
Audio			
Audio Compression	G.711A		
Interface			
Video Input	4*BNC	8*BNC	16*BNC
Video Output	1*VGA,1*HDMI		
Audio I/O	4/1	8/1	16/1
Alarm I/O	4/1	4/1	16/4
Ethernet	1*10/100Mbps Ethernet port, RJ45 port		1*10/100M/1000Mbps Ethernet port, RJ45 port
PTZ Control	1*RS485, Support for multiple PTZ protocol		1*RS485, 1*RS232,Support for multiple PTZ protocol
USB	2*USB2.0		
Max HDD	2*8TB		
General			
Temperature	0 °C - + 55 °C		
Humidity	10% -90% RH		
Power	12V/4A		
Consumption	<15W(Without HDD )		
Dimension	310mm(L)* 298mm(W)* 60mm(H)		

JF TECH Co.,Ltd.

Headquarters(Hangzhou):

Building 9, Yinhu Innovation Center, Hangzhou, China

Business Center(Shenzhen):

A 7th Floor, Block Sakata 5 Avenue and Chong Hing Times Tower Shenzhen

All Rights Reserved • Specifications subject to change without notice.

Website:<http://www.jftech.com>

Tel:+86-0571-23271188

Tel:+86-0755-32898088