

# JF-ADVR-K7216/K7232

## 16ch/32ch Fribrid 1080P 8HDD ADVR



## Features

- ◆ Support 16ch/32ch 1080P Unreal-time Encoding
- ◆ Support AHD/TVI/CVI/CVBS/IP Self-adaptive
- ◆ HDMI/VGA Simultaneous Video Output
- ◆ Support DHCP,FTP,DNS,DDNS,NTP,UPNP,EMAIL,3G,WIFI
- ◆ Support ONVIF Protocol
- ◆ Support WEB,VMS,MYEYE Platform
- ◆ Support Mobile Phone Monitoring(IOS ,Android)
- ◆ Cloud Services,P2P,Alarm Information Push To Phone
- ◆ Support Multi-Language

## Dimensions



# JF-ADVR-K7216/K7232

16ch/32ch Fribrid 1080P 8HDD ADVR

## Specification

8HDD		
Model	JF-ADVR-K7216	JF-ADVR-K7232
Video		
Encode	16CH*1080P@12fps	32CH*1080P@15fps
Playback	16CH*1080P@12fps	16CH*1080P@15fps
Multi-Mode	Analog	16CH*1080P
	Hybrid	8CH*1080P(Analog)+8CH*1080P(IP)
	IP	32CH*1080P/16CH*3M /8CH*5M
Video Compression	H.264/H.264+	
Audio		
Audio Compression	G.711A	
Interface		
Video Input	16*BNC	32*BNC
Video Output	1*HDMI.1*VGA	
Audio I/O	16/1	
Alarm I/O	16/4	
Ethernet	1*10/100M/1000Mbps Ethernet port, RJ45 port	
PTZ Control	1*RS485,1*RS232, Support for multiple PTZ protocol	
USB	2*USB2.0	
Max HDD	8*8TB	
General		
Temperature	0 °C - + 55 °C	
Humidity	10% -90% RH	
Power	ATX	
Consumption	<15W(Without HDD )	
Dimension	443mm(L)*427.5mm(W)*92mm(H)	

JF TECH Co.,Ltd.

Headquarters(Hangzhou):

Building 9, Yinhu Innovation Center, Hangzhou, China

Business Center(Shenzhen):

A 7th Floor, Block Sakata 5 Avenue and Chong Hing Times Tower Shenzhen

All Rights Reserved • Specifications subject to change without notice.

Website:<http://www.jftech.com>

Tel:+86-0571-23271188

Tel:+86-0755-32898088